



Coor II 960

80 16 67



ANNUAL REPORT

on

THE ACTIVITY OF Limnoria tripunctata
IN PILING CUT-OFFS FROM
NAPHTHALENE-ENRICHED CREOSOTED PILINGS

to

UNITED STATES DEPARTMENT OF THE NAVY
OFFICE OF NAVAL RESEARCH
MICROBIOLOGY BRANCH
CONTRACTS #NOO014-79-C-0667
TASK NO. NR 205-034

December 19, 1980



bу

C.I. Belmore

Report No. 15021

BATTELLE

New England Marine Facility
The William F. Clapp Laboratories
Duxbury, Massachusetts 02332

Reproduction in whole or in part is permitted for any purpose of the United States Government. This document has been approved for public release; its distribution is unlimited. SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER 2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
NR 205-034 AD -A 0 93 31	8
A. TITLE (and Substitle)	5. TYPE OF REPORT & PERIOD COVERED
The Activity of Limnoria tripunctata in Piling Cut-offs from Naphthalene-enriched Creosoted	Annual 8/1/79-11/1/80
Pilings.	6 PERFORMING OBG. REPORT NUMBER
7. AUTHOR(e)	8. CONTRACT OR GRANT NUMBER(4)
10 C. Irene/Belmore	NØØØ14-79-C-Ø667
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
Battelle	124126
New England Marine Facility	NR 205-034
The William F. Clapp Laboratories ,	NK 203-034
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE
Office of Naval Research	12/19/80
Microbiology Branch - Code 443 800 N. Quincy Street	13. NUMBER OF PAGES
800 N. Quincy Street	18
Arlington Virginia 22217 14. MONITORING AGENCE NAME & ADDRESS(If different from Controlling Office)	15. SECURITY CLASS, (of this report)
Arraal ceft. 1 Aug 19-	Unclassified
1 Nev 89)	15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report)	

Approved for Public Release; Distribution Unlimited

17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)
Limnoria tripunctata
Piling Cut-offs
Naphthalene-enriched Creosote
Pholadidae

20. ABSTRACT (Continue on reverse side if necessary and identify by block number)

**Cut-offs from piling treated with creosote plus additional naphthalene at four levels were exposed to Limnoria tripunctata both in the laboratory and in the field. After one year of exposure, laboratory exposures indicate 10% and 20%

additives to be more resistant to borer attack than the 30% and 40% additive samples. Field studies showed the 30% additive provided the best protection.

The molluscan borer Pholadidae entered all discs exposed under field conditions

DD 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE \$/N 0102-LF-014-6601

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered

00/6=0

TABLE OF CONTENTS

			Page
MANAC	GEMENT	SUMMARY	. i
INTRO	DUCT	ION	. 1
OBJEC	CTIVES	5	. 1
MATER	RIALS	AND METHODS	. 2
	Labor	catory Exposures	. 2
	Field	l Exposures	. 2
RESUL	TS AN	TD DISCUSSION	. 3
	Serie	es l - Laboratory Exposures	. 3
		es 2 - Laboratory Exposures	
		es 1 - Field Exposures	
		es 2 - Field Exposures	
		rison of Field and Laboratory Exposures	
		ited Wedges	
	water	Temperature	. 10
		LIST OF TABLES	
Table	1.	Order of Disc Placement on Rod, for Field Exposures of Daytona Beach, Florida	. 4
Table	2.	Number of Limnoria Tunnels in Wedges on Laboratory Exposure - Series 1	. 5
Table	3.	Mean Number of Limnoria Tunnels in Laboratory Wedges After 5 to 12 Months of Exposure	. 7
Ta ble	4.	Area of Surface Exposed to Limnoria tripunctata of Series 1 Coated Wedges in Square Centimeters	. 9
Table	5.	Number of Limnoria Tunnels in Wedges on Laboratory	10

LIST OF TABLES (continued)

		Page
Table	6.	Number of Limmoria Tunnels in Discs on Field Exposure 11
Table	7.	Number of Specimens on Pholadidae in Discs on Field Exposure
Table	8.	Mean Number of Marine Borers in Discs and Reconstituted Discs
Table	9.	Laboratory Water Temperatures °C From November, 1979 Through October, 1980
Table	10.	Daytona Beach Water Temperatures °C From September, 1979 Through September, 1980

NTIS PTIC	ion For GRA&I TAB ounced fication		
By Dist		ty Codes and/or cial	1

MANAGEMENT SUMMARY

Cut-offs from piling treated with creosote plus additional napthalene at four levels were exposed to *Limnoria tripunctata* both in the laboratory and in the field.

After one year of exposure to active *Limnoria* attack in the laboratory, the coated wedges from the 10 percent naphthalene additive showed the greatest resistance to attack by *Limnoria tripunctata*.

The treatment which showed the least resistance to Limnoria tripunctata under laboratory conditions was the 30 percent additive.

In Series 1, which has had one year of exposure, the 30 percent naphthalene creosote discs showed the best resistance to *Limnoria* attack under field conditions and the 20 percent additive discs were most severely attacked. The 30 percent additive discs which were submerged for six months showed a heavier *Limnoria* attack than any of the discs exposed for 12 months.

Fouling organisms, especially barnacles were very heavy on all the discs exposed under field conditions.

During the September, 1980 inspection, molluscan borers (Pholadidae) were found in all treatments exposed at Daytona Beach, Florida. No significant variations were observed among the four treatments.

After one year of exposure to Limnoria tripunctata attack, both in the field and in the laboratory, the piling cut-offs with four different percentages of naphthalene plus creosote are all showing susceptibility to Limnoria attack. A longer exposure period should ascertain whether the initial trends will continue at the same rate.

THE ACTIVITY OF Limnoria tripunctata IN PILING CUT-OFFS FROM NAPHTHALENE-ENRICHED CREOSOTED PILINGS

by

C.I. Belmore

INTRODUCTION

The need for an improved treatment for marine pilings has been recognized by both the United States Navy and industry. A satisfactory improved treatment must result in piling that will effectively prevent marine borer attack, resist breakage in handling and driving, and be economically feasible. Creosote-impregnated piling satisfies these needs except in areas where the wood-boring crustacean, Limmoria tripunctata exists, since L. tripunctata is relatively resistant to creosote.

Much has been accomplished in recent years towards improvement of treatments and development of new preservatives against borers and other destructive elements. Through cooperative efforts of industry and the Navy, a working-test exposure was installed in 1978 at Roosevelt Roads, Puerto Rico using piling treated with creosote containing the additive naphthalene in ranges of 10 to 40 percent. The piling cut-offs produced during this installation are being used for laboratory and field exposures to determine the preservative effectiveness of the added naphthalene.

OBJECTIVES

The objectives of this study are to determine the preservative effectiveness of various percentages of naphthalene-enriched creosote treatments exposed to Limnoria tripunctata attack in the laboratory and in a natural seawater environment; to determine if Limnoria attack is accelerated by exposure in the laboratory and to investigate if there are any seasonal differences in the rate of Limnoria attack in a natural environment where molluscan borers are also present.

MATERIALS AND METHODS

Three-inch discs from pile cut-offs were received at Battelle's New England Marine Facility - The William F. Clapp Laboratories in Duxbury, Massachusetts for laboratory exposure and at Battelle's Florida Marine Research Facility in Daytona Beach, Florida for field exposure. A total of 38 discs, nine treated with 10 percent naphthalene creosote, 10 with 28 percent naphthalene creosote, 10 with 30 percent naphthalene creosote, and nine with 40 percent naphthalene creosote were to be used.

Laboratory Exposures

Three discs from each treatment were cut into eight pie-shaped segments, the heartwood removed, and the resulting wedge coated with Koppers Bitumastic 300 M on all surfaces expect the outside circumferal surface. The uncoated surface of these wedges represents the area normally exposed to Limmoria attack on pilings. A fourth disc from each treatment was also cut into eight segments but was not coated. These wedges have the area normally inside a piling exposed to Limmoria attack also.

Twelve coated and four uncoated wedges per treatment were exposed to active *Limnoria tripunctata* attack in flowing seawater tables in the laboratory on October 31, 1979. An untreated soft pine coupon, measuring 73 mm x 103 mm x 18 mm, was added to each table to serve as a control. These samples comprosed Series 1.

The second series of samples was placed in laboratory water tables on March 24, 1980, during a normally heavy Limnoria migrating season (March-April). During preparation of the discs on October 9, 1979, two of the discs were spoiled. Since replacements were not received, the second set of exposures was not a complete replicate of the first set. Only the 10 percent and 40 percent naphthalene creosote discs were available for the second series. Preparation and method of exposure were the same as used in Series 1.

Field Exposures

The cross-section surfaces of 16 discs (four per treatment) were drilled with a 5/8" (16 mm) center hole, coated with Koppers

Bitumastic 300 M on the sawn surfaces, mounted on four galvanized steel rods, and submerged vertically in the natural seawater environment at the Florida Marine Research Facility at Daytona Beach, Florida. Each rod held one disc from each treatment simulating an in-place piling. Four rods and discs for Series 1 were installed September 17, 1979; the remaining discs received were installed on two rods with three discs each for Series 2 on March 27, 1980. The order of arrangement of discs on the rods is shown in Table 1.

RESULTS AND DISCUSSION

Series 1 - Laboratory Exposures

Inpsections for *Limnoria* attack were performed monthly. The results of these inspections are shown in Table 2.

All treated wedges remained free of Limnoria tripunctata for over two months. By the end of the three-month exposure period, Limnoria had started tunneling into two of the coated 10 percent naphthalene cressote wedges. With the exception of one of the 20 percent naphthalene creosote coated wedges which had one tunnel after three and four months exposure, and two tunnels at five months, none of the other wedges except the 10 percent coated wedges were attacked by Limnoria until after six months of exposure.

The wedges with the 10 percent naphthalene were the first to be attacked by *Limnoria* but this early attack did not continue to increase at the same rate as the attack in the other treatments.

The rate of increase in the *Limnoria* attack from the eight month inspection to the twelth month inspection was 3 percent for the 10 percent additive, 61 percent for the 20 percent additive, 39 percent for the 30 percent additive and 47 percent for the 40 percent additive.

At the inspection after one year of exposure to active Limmoria attack in the laboratory, the coated wedges from the 10 percent naphthalene additive showed the greatest resistance to attack by Limmoria tripunctata with a mean of 27 tunnels per wedge (Table 3). Four of the coated wedges were still without any Limmoria attack at the end of one year of exposure.

TABLE 1. ORDER OF DISC PLACEMENT ON ROD, FOR FIELD EXPOSURES OF DAYTONA BEACH, FLORIDA

	Set						
1	2	3	4	5	6		
10%	20%	30%	40%	30%	20%		
20%	30%	40%	10%	20%	30%		
30%	40%	10%	20%	20%	20%		
40%	10%	20%	30%				

Sets 1-4 installed September, 1979. Sets 5-6 installed March 27, 1980.

TABLE 2. NUMBER OF *Limnoria* TUNNELS IN WEDGES ON LABORATORY EXPOSURE - SERIES 1

	Sample												
Treatment	Number	1_	2	<u>3</u>	11	5	6	7	8	9	10	11	12
	1			9	11	14	27	27	27	27	27	27	40
	2 3 4 5 6						1	1	1	1	1	1	2
10%	3												
Naphthalene	4								12	19	19	21	31
Naphthalehe Creosote	5												
	6												
(Coated)	7			67	70	70	70	70	70	70	70	70	73
	8					2	2	2	2	2	12	53	105
	9					_	_	_	_	-	~-		
	10						4	4	4	4	4	4	12
	11						4	**	4	7		13	42
	12										7		
	12										1	4	18
	1												
10%	2 3	_		13	13	15	15	15	15	15	15	15	23
(Uncoated)	3	•		15	15	15	15	15	15	15	15	15	48
	4			7	7	7	12	12	12	12	13	17	51
	1												2
													_
	3												
20%	2 3 4											7	1
	4						•	,	,	,	-	1	1
Napthalene	5 6						1	1	1	1	5	17	44
Creosote	6												45
(Coated)	7												7
	8										9	18	36
	9						3	3	4	7	11	33	90
	10			1	1	2	2	2	2	3	29	48	110
	11										10	26	71
	12										3	19	35
	1										5	18	67
20%	2					4	4	4	4	4	4	7	120
(Uncoated)	3					4	7	~	7	-	3	9	
(oncoated)	4										1	8	88
	4										1	٥	37
	1								2	4	28	100	200
	2 3										1	7	28
	3						5	5	5	5	6	9	4
30%	4								1	3	14	38	70
Naphthalene	5 6						4	4	6	32	100	205	290
Creosote	6						19	19	22	86	100	130	18
(Coated)	7						2	2	16	60	140	200	300
· · · · · · · · · · · · · · · · · · ·	8					•		-	2	31	40	110	140
	8 9						1	1	1	1	2	12	3!
	10						12	13	20	130	190	300	360
	10						8	8	32	92			
							ō	ō	32		130	210	275
	12									2	11	30	7:

-

TABLE 2. (continued)

	Sample												
Treatment	Number	1_	2	3	4	5	6	7	8	9	10	11	12
	1					-			11	65	100	210	250
30%	2						30	30	110	300	320	350	400
(Uncoated)	3						38	38	60	160	200	300	390
	4						8	14	35	65	110	160	190
	1											•	4
	2 3										3	18	26
	3												6
40%	4										1	7	22
Naphthalene	5										4	12	14
Creosote	6												3
(Coated)	7										4	14	32
	8										2	5	10
	9										33	75	140
	10										26	80	130
	11									7	50	200	300
	12						9	9	21	90	110	200	320
40%	1					6	40	45	70	300	325	350	450
Naphthalene	2						10	12	50	140	150	210	260
Creosote	3						12	17	60	125	200	300	475
(Uncoated)	4						19	39	90	280	285	300	380

TABLE 3. MEAN NUMBER OF Limnoria TUNNELS IN LABORATORY WEDGES AFTER 5 TO 12 MONTHS OF EXPOSURE

						Months			
Series 1	No.	5	6	7	8	9	10	11	12
1	10% Coated	7.2	8.7	8.7	9.7	10.3	11.8	16.1	27
	10% Uncoated	9.3	9.3	9.3	9.3	9.3	10.8	11.8	30.5
	20% Coated	0.2	0.5	0.5	0.6	0.9	5.6	13.5	36.6
	20% Uncoated	1.0	1.0	1.0	1.0	1.0	3.3	10.5	78.0
	30% Coated	0.0	4.3	4.3	8.9	37.2	63.5	112.3	166.8
	30% Uncoated	0.0	19.0	20.5	54	147.5	182.5	255	307.5
	40% Coated	0.0	0.0	0.0	1.8	8.1	19.4	50.9	83.9
	40% Uncoated	1.5	20.3	28.3	67.5	211.3	240	290	391.3
2									
	10% Coated	1.7	5.5	5.5					
	10% Uncoated	0	0	.25					
	40% Coated	0	0	2.4					
	40% Uncoated	17	52	83					

The amount of attack in the 20 percent naphthalene additive wedges was very similar to that in the 10 percent wedges with a mean of 37 *Limnoria* tunnels per wedge after one year of exposure. Two of these wedges were free of any attack.

The treatment which showed the least resistance to *Limnoria* tripunctata under laboratory conditions was the 30 percent additive. These wedges all showed *Limnoria* tunnels present with a mean of 167 tunnels per wedge.

Wedges with a 40 percent naphthalene additive, with a mean of 84 tunnels per wedge, stood up better than the 30 percent additive but not as well as the 10 percent and 20 percent.

Variance in the size of the piling cut-offs and resulting wedges is shown in Table 4. Taking this size difference into consideration, the ratio of numbers of *Limnoria* tunnels per square centimeter of exposed surface of coated wedges in the laboratory was 10 percent = 0.29, 20 percent - 0.34, 30 percent = 1.58, 40 percent = 1.30.

Series 2 - Laboratory Exposures

Complete replicate samples of the four treatments exposed in October, 1979 were not available. Series 2, therefore consists of 12 coated wedges and four uncoated wedges of the 10 percent and 40 percent treatments only. Results of the monthly inspections are shown in Table 5.

After six months of exposure, the results of these inspections are similar to those of Series 1 at six months. Four of the 10 percent coated wedges have been attacked by *Limnoria*; none of the 40 percent coated wedges and all of the 40 percent uncoated wedges show attack.

Series 1 - Field Exposures

At the sixth-month inspection of the discs on exposure at Daytona Beach, Florida, a few *Limnoria* had started tunneling in one of the 20 percent naphthalene creosote and one of the 40 percent naphthalene creosote piling cut-offs (Table 6).

TABLE 4. AREA OF SURFACE EXPOSED TO Limnoria tripunctata OF SERIES 1 COATED WEDGES IN SQUARE CENTIMETERS

Wedges	10%	20%	30%	40%	
1	105	115	114	74	
2	119	125	112	82	
3	121	104	118	88	
4	. 130	67	108	65	
5	113	117	102	63	
6	106	122	104	103	
7	114	105	117	86	
8	124	132	108	72	
9	80	99	104	103	
10	125	122	·128	106	
11	96	113	100	79	
12	135	102	106	111	
Cotals	1,368	1,323	1,321	1,032	

TABLE 5. NUMBER OF *Limmoria* TUNNELS IN WEDGES ON LABORATORY EXPOSURE - Series 2

	Sample					·	
Treatment	Number	1	2	3	4	5	6
	1					14	فاند
	1 2					2	11
10%	3					-	
Naphthalene	4					2	3
Creosote	5					2	3 2
(Coated)	5 6					_	_
(552552)							
	7 8 9						
	9						
	10						
	11						
	12						
	1						
10%	1						
(Uncoated)	2 3						
(Uncoated)	4						
	₹						
	1 2 3 4						
	2						
	3						
40%	4						
Naphthalene	5 6						
Creosote	6						
(Coated)	7						
	8						
	9						•
	10						
	11						
	12						
	1				6	9	18
40%	2					26	70
(Uncoated)	1 2 3 4					19	40
,,	4			2	13	14	80

TABLE 6. NUMBER OF Limnoria TUNNELS IN DISCS ON FIELD EXPOSURE

	Months		Treatme	ent		
Set	Exposed	10%	20%	30%	40%	
1	6	0	0	0	0	
	12	100	600	800	1300	
2	6	0	10	0	0	
	12	1000	1300	400	1000	
3	6	0	0	0	6	
	12	4000	5500	200	1000	
4	6	0	0	0	0	
	12	500	600	350	1300	
5	6	-	1800	2000	-	
			3000			
6	6		Lost	4000	-	
			Lost			

When inspected again after 12 months of exposure, all discs showed trace to moderate attack by Limmoria as well as a trace attack by Pholadidae (Tables 6 and 7).

The Limmoria attack in the 10 percent and 20 percent discs showed great variation. The number of tunnels in the 10 percent additive discs ranged from 100 in Set 1 to 4000 in Set 3. In the 20 percent additive discs, the range was 600 tunnels in Sets 1 and 4 to 5500 tunnels in Set 3. The variation among discs was not as great in the other two treatments. The range in the 30 percent discs was 200 tunnels in Set 3 to 800 tunnels in Set 1. Very little difference in attack was observed in the 40 percent discs. Sets 2 and 3 had 1000 Limmoria tunnels and Sets 1 and 4 had 1300 Limmoria tunnels.

Most of the discs had one to six specimens of the boring mollusc, Pholadidae, at the 12-month inspection. This is not a very heavy pholad attack but does indicate the treatments are not a deterrent to this molluscan borer.

The 30 percent naphthalene creosote discs showed the greatest resistance to Limnoria attack under field conditions with a mean of 438 tunnels per disc. The 20 percent disc was most severely attacked, with a mean of 2000 Limnoria tunnels per disc. The mean number of tunnels in the 10 percent additive was 1600, and there were 1150 tunnels in the 40 percent additive.

Series 2 - Field Exposures

Four 20 percent and two 30 percent naphthalene enriched creosoted pile cut-offs were submerged at Daytona Beach, Florida in March, 1980. At the six-month inspection, two of the 20 percent treatments from Set 6 were missing. The remaining discs all showed light to moderate *Limmoria* attack.

The two 30 percent discs were more severely attacked in six months of exposure than the 30 percent discs in Series 1 which had been on exposure for 12 months (Table 6). These two discs showed a mean of 3000 tunnels per disc which is greater than any of the discs which were in Series 1.

TABLE 7. NUMBER OF SPECIMENS OF PHOLADIDAE IN DISCS ON FIELD EXPOSURE

		Treatmen		
Set*	10%	20%	30%	40%
1	o	1	1	1
2	2	2	1	3
3	4	6	3	3
4	. 2	3	2	2
5	-	2	0	-
6	<u>-</u>	-	2	-

^{*} Sets 1-4 on exposure for 12 months, Sets 5-6 exposed for 6 months.

The field samples were heavily fouled with barnacles and other organisms both at the six-month and twelve-month inspection periods. At the March 27, 1980 inspection, all discs were covered with very heavy settlement of barnacles with traces of Hydroid, Amphipods, and Annelida. In September, 1980, the heavy fouling was dominated by barnacles with traces of Hydroid, Amphipods, Ascidians, Crassostrea and filamentous bryozoan. As much fouling as possible was removed at the time of the inspections.

Laboratory samples were inspected monthly and all fouling removed. No barnacles became attached to these samples. Very little fouling except for a slime film and a few Ascidians was present on these exposures.

Comparison of Field and Laboratory Exposures

After 12 months of exposure to Limmoria tripunctata in the laboratory and in the field, the creosoted piling cut-offs with naphthalene added were all attacked by gribbles. Field and laboratory exposures have indicated different results after one year. The 30 percent naphthalene cut-offs were the most successful in the field and were the least successful in the laboratory (Table 8).

In the field exposures, the order of best protection was 30, 40, 10, and 20 percent, respectively.

In the laboratory exposures, the order of best protection was 10, 20, 40, and 30 percent, respectively.

The 30 percent discs submerged in March, 1980 show a much heavier Limmoria attack than any of the discs submerged for one year.

Uncoated Wedges

The number of Limmoria tunnels in the uncoated wedges was not included in the overall assessment of effectiveness of the four treatments.

These wedges generally showed heavier attack than coated wedges. By not coating the cut surface with Bitumastic 300 M, surfaces not exposed

TABLE 8. MEAN NUMBER OF MARINE BORERS IN DISCS
AND RECONSTITUTED DISCS
(Discs submerged 12 months.)

10%	20%	30%	40%
1600	2000	438	1150
2	3	1.75	2.25
33	37	167	84
31	78	308	392
264	295	1341	675
244	624	2460	3130
	1600 2 33 31 264	1600 2000 2 3 33 37 31 78 264 295	1600 2000 438 2 3 1.75 33 37 167 31 78 308 264 295 1341

to Limnoria attack in actual pilings were attacked by Limnoria. The destruction was increased by borers first entering the cut surface areas before they started burrowing into the edges of the outside piling surface area (Table 8).

Water Temperature

Water temperatures in the laboratory exposures ranged from a low of 10°C to a high of 32.5°C (Table 9). Both of these extremes were in December, 1979. During the period from October to June, the laboratory sea water passes through a heat exchanger in order to maintain temperatures that will support the breeding of *Limnoria* all year.

The average temperature of the laboratory sea water during the period these discs were exposed to active *Limnoria* attack was 19.3°C.

The discs submerged at the Florida Marine Research Facility in Daytona Beach, Florida were subjected to a low of 11°C and a high of 28°C (Table 10). The average water temperature at the field site was 21.6°C during the period from September, 1979 to September, 1980.

TABLE 9. LABORATORY WATER TEMPERATURES °C FROM NOVEMBER, 1979 THROUGH OCTOBER, 1980

	High	Low	Average
1979			
November	22.5	15.5	19.9
December	32.5	10.0	18.4
1980			
January	22.5	16.5	19.1
February	22.5	14.0	18.6
March	27.0	15.5	19.3
April	21.5	18.5	19.9
May	22.5	18.0	20.9
June	20.0	18.0	19.3
July	21.0	17.5	18.9
August	22.5	18.5	20.1
September	21.5	14.0	18.0
October	20.5	15.5	18.8

Temperature readings based on daily 9:00 AM readings from Taylor Temperature Recorder.

TABLE 10. DAYTONA BEACH WATER TEMPERATURES °C FROM SEPTEMBER, 1979 THROUGH SEPTEMBER, 1980

	Udah	I and	A
	High	Low	Average
1979			
September	27	25	25.4
October	27	22.5	24.8
November	24	18	21.3
December	20	15.5	17.8
<u>1980</u>			
January	17.5	12	15.4
February	14	11	12.5
March	20	11	18.2
April	22	19	20.3
Мау	24.5	20.5	21.7
June	27.5	24	25.6
July	28	24.5	26.3
August	27	24	26
September	27.5	24	26.1

OFFICE OF NAVAL RESEARCH NAVAL BIOLOGY PROJECT STANDARD DISTRIBUTION LIST

Number of Copies

(12)

Administrator
Defense Technical Information Center
Cameron Station
Alexandria, VA 22314

(6)

Director Naval Research Laboratory Attn: Technical Information Division Code 2627 Washington, DC 20375

(3)

Office of Naval Research Naval Biology Project Code 443 800 N. Quincy Street Arlington, VA 22217

One copy to each of the following:

Office of Naval Research Code 200 800 N. Quincy Street Arlington, VA 22217

Office of Naval Research Eastern/ Central Regional Office Building 114, Section D 666 Summer Street Boston, MA 02210

Office of Naval Research Branch Office 536 South Clark Street Chicago, IL 60605

Office of Naval Research Western Regional Office 1030 East Green Street Pasadena, CA 91106

Technical Library U.S. Army Natick Laboratories Natick, MA 01760 Dr. A.L. Salfkosky Scientific Advisor, Commandant of Marine Corp (Code RD-1) Washington, DC 20380

Assistant Commander for Research & Development Code 03 Naval Facilities Engineering Command 200 Stovall Street Alexandria, VA 22332

Biological Sciences Staff Code 112B Naval Facilities Engineering Command 200 Stovall Street Alexandria, VA 22332

Scientific Library Naval Biosciences Laboratory Naval Supply Center Oakland, CA 94625

STANDARD DISTRIBUTION LIST (Cont'd)

Commander Army Research Office Research Triangle Park, NC 27709

Technical Advisory Division National Marine Fisheries Service Department of Commerce

Head, Disease Vector Control Section BUMED (MED-31412) Department of the Navy Washington, DC 20372

Matthew Stevenson National Academy of Sciences Room JH 538 2101 Constitution Avenue Washington, DC 20418

Alexander, Dr. Martin Department of Agronomy Cornell University Ithaca, New York 14850 NR 205-032 N00014-78-C-004

Colwell, Dr. Rita R.
Department of Microbiology
University of Maryland
College Park, Maryland 20742
NR 133-081
N00014-75-C-0340

DePalma, Mr. John National Space Technology Lab Building 1105, Room C-316 NSTL Station, Mississippi 38522 NR 205-006 N0001479WR90115

Fahlstrom, Mr. G.B. Osmose Wood Preserving Company 980 Ellicot Street Buffalo, New York 14209 NR 205-036 N00014-80-G-0033

Belmore, C. Irene
Battelle Columbus Laboratories
William F. Clapp Laboratories, Inc.
Washington Street
Duxbury, Massachusetts 02332
NR 205-034
N00014-79-C-0667

Commanding Officer
Naval Medical Research & Development
Command, Code 47
National Naval Medical Center
Bethesda, MD 20014

Commandant, DAT U.S. Coast Guard 400 Seventh Street, SW Washington, DC 20511

Commandant, DAS
U.S. Coast Guard Research & Development
Center
Avery Point
Groton, CT 06340

Commander Naval Oceanography Command NSTL Station Bay St. Louis, MS 39529

Officer in Charge Navy Disease Vector Ecology & Control Center Naval Air Station Alameda, CA 94501

Officer in Charge Navy Disease Vector Ecology & Control Center Naval Air Station Jacksonville, FL 32212

David W. Taylor Naval Ship Research & Development Center Code 286 Annapolis, MD 21402

David W. Taylor Naval Ship Research & Development Center Code 2856 Annapolis, MD 21402

Mitchell, Dr. Ralph Harvard University Division of Engineering and Applied Physics Cambridge, Massachusetts 02138 NR 205-002 N00014-76-C-0262

STANDARD DISTRIBUTION LIST (Cont'd)

Romanovsky, Dr. V.
Centre de Recherches et d'Etudes
Oceanographiques
73-77, rue de Sevres
92100 Boulogne, FRANCE
NR 205-016
N00014-78-M-0034

Vedros, Dr. Neylan A. Scientific Director Naval Biosciences Laboratory Naval Supply Center Oakland, California 94625 NR 205-001 N00014-75-C-0774

Guard, Dr. Harold E. Naval Biosciences Laboratory Naval Supply Center Oakland, California 94625

Laughlin, Dr. Roy Naval Biosciences Laboratory Naval Supply Center Oakland, California 94625

DA FIL